EC Sense Selection Guide

2 models · downloadable datasheets also available per model on anchorsensor.com

TB200B-EC4-Cl2-5 — TB200B-EC4-Cl2-5 Chlorine Detection Module

The EC Sense TB200B-EC4-Cl2-5 is an industrial-safety-grade smart digital gas sensor module for Chlorine detection, with a 0 – 5 ppm range and 0.001 ppm resolution. The module uses an EC4 electrochemical sensor (40 × 30 × 22.45 mm including sensor, under 25 g)…

Target Gas	Chlorine
Detection Range	0 – 5 ppm
Resolution	0.001 ppm
Sensor Packaging	EC4
Order No. (UART)	04-TB200B-EC4-Cl2-5-01
Order No. (I²C)	04-TB200B-EC4-Cl2-5-I2C-01
Operating Principle	Solid Polymer Electrochemical Sensing Technology
Accuracy	± 5% (measurement value)
Repeatability	1%
Linearity	Linear
Long-Term Drift	< 5% / year
Expected Lifetime	> 5 years
Output Signal	UART (TTL 3.3 V) or I²C digital signal
UART Parameters	Baud rate 9600, 8 data bits, 1 stop bit; VCC red / GND black / RX yellow / TX green
I²C Parameters	Frequency ≤ 20 kHz, signal voltage 3.3 V; VCC red / GND black / SDA yellow / SCL green
Communication Mode	Active-upload and question-answer modes; Q&A is the default on power-up
Built-in Temperature Sensor	-20 ℃ to +70 ℃, ± 0.2 ℃ (typical)
Built-in Humidity Sensor	0 – 100% RH, ± 2% (typical)
Working Temperature	-40 ℃ to +55 ℃
Working Humidity	15 – 95% RH (non-condensing)
Working Pressure	Atmospheric pressure ± 10%
Size (Including Sensor)	40 × 30 × 22.45 mm
Size (Without Sensor)	40 × 30 × 5.6 mm
Weight	< 25 g (including sensor)
Cable Length	100 mm, special length by request
Warranty	12 months from the date of shipment

Every module is professionally calibrated with standard gas before shipment, with the calibration data stored in its flash chip — plug-and-play, no secondary gas calibration required. Refer to the dat

TB200B-EC4-Cl2-50 — TB200B-EC4-Cl2-50 Chlorine Detection Module

The EC Sense TB200B-EC4-Cl2-50 is an industrial-safety-grade smart digital gas sensor module for Chlorine detection, with a 0 – 50 ppm range and 0.01 ppm resolution. The module uses an EC4 electrochemical sensor (40 × 30 × 22.45 mm including sensor, under 25 g…

Target Gas	Chlorine
Detection Range	0 – 50 ppm
Resolution	0.01 ppm
Sensor Packaging	EC4
Order No. (UART)	04-TB200B-EC4-Cl2-50-01
Order No. (I²C)	04-TB200B-EC4-Cl2-50-I2C-01
Operating Principle	Solid Polymer Electrochemical Sensing Technology
Accuracy	± 5% (measurement value)
Repeatability	1%
Linearity	Linear
Long-Term Drift	< 5% / year
Expected Lifetime	> 5 years
Output Signal	UART (TTL 3.3 V) or I²C digital signal
UART Parameters	Baud rate 9600, 8 data bits, 1 stop bit; VCC red / GND black / RX yellow / TX green
I²C Parameters	Frequency ≤ 20 kHz, signal voltage 3.3 V; VCC red / GND black / SDA yellow / SCL green
Communication Mode	Active-upload and question-answer modes; Q&A is the default on power-up
Built-in Temperature Sensor	-20 ℃ to +70 ℃, ± 0.2 ℃ (typical)
Built-in Humidity Sensor	0 – 100% RH, ± 2% (typical)
Working Temperature	-40 ℃ to +55 ℃
Working Humidity	15 – 95% RH (non-condensing)
Working Pressure	Atmospheric pressure ± 10%
Size (Including Sensor)	40 × 30 × 22.45 mm
Size (Without Sensor)	40 × 30 × 5.6 mm
Weight	< 25 g (including sensor)
Cable Length	100 mm, special length by request
Warranty	12 months from the date of shipment

Every module is professionally calibrated with standard gas before shipment, with the calibration data stored in its flash chip — plug-and-play, no secondary gas calibration required. Refer to the dat